

Parking Area Criteria

Stall Dimensions	Allowed front overhang	Park Angle (A)	Minimum Aisle Width (D)	Parking Row Depth w/o overhang (C)	Parking Row Depth w/ overhang	Total depth reduction for abutting inner rows	Stall Width at curb (B)	Excess curb length at row end
9.0' x 19'	1.5'	90°	24'	19.0'	17.5'	0'	9.0'	0'
		60°	18' *	21.0'	19.7'	2.25'	10.4'	12.1'
		45°	13' *	19.8'	18.8'	3.2'	12.7'	19.8'
9.5' x 18'	1.5'	90°	24'	18.0'	16.5'	0'	9.5'	0'
		60°	18' *	20.4'	19.0'	2.4'	11.0'	11.8'
		45°	13.5' *	19.5'	18.2'	3.4'	13.4'	19.5'

Parallel parking space: 8.0' x 23.0' with 14' one-way aisle or 24' two-way aisle

Note 1: Front overhang is only allowed for outer row spaces.

Note 2: Where curb is not provided, wheelstop must be provided for each outer row space.

Note 3: Where parking abuts sidewalk, provide 2' min. clear zone between curb/wheelstop and sidewalk travel way.

Note 4: Where different sized spaces are used within a row, the depth adjustment cannot be made at the aisle.

Note 5: Where an 18' deep space is located between two 19' spaces, the 18' space must be 10' wide.

* For one-way aisle